



At a glance:

- ✓ Multilingualism within a guided group
- ✓ Dual-speaking function for two guides in parallel
- ✓ Extremely small, light and robust
- ✓ User-friendly, intuitive user interface
- ✓ Integrated GPS system
- ✓ Transport bag, charging station and transmission system in one
- ✓ Windows GroupySync is used for processing, synchronising and managing your content:
 - a) Text-to-speech: Text is converted into an MP3 file
 - b) 18 languages, different accents (e.g. British English, American English)
 - c) Male or female voice output
- ✓ Custom branding is possible
- ✓ Theft protection on request as accessory
- ✓ Versatile applications for an even better experience

For which applications is GroupyCompany suited?

Audioguide GroupyCompany is a useful addition for anyone who intends to spice up their guided tours even more. This feature makes it possible to play audio during the tour. A function your international guests will find particularly useful when touring your premises. Use the dual function to transfer ready-made content to the device and play it back in any number of languages. Playback occurs with individual numbering and selection or for all visitors at the same time via the tour guide's controller tag.

How do I use GroupyCompany?

The GroupyCompany system consists of a tag for the guide and a controller tag for the guide. Different headphones can be connected to them. With the Windows software GrouySync, included in delivery, you can use the charging station CS25 or CS56 to conveniently copy and edit content.

Guide



Guest



Technical specifications

GroupyCompany tag

Working frequency	2390 - 2507 MHz
Radiated power	<20 mW on average
Weight	90g
Size	95 x 60 x 13 mm
Internal battery	LiPo 3.7V, 2000mAh, approx. 13 hours streaming
Storage space	Approx. 2 GB of content (corresponds to approx. 4000 minutes)
Supported audio format	MP3, CBR 128 kbps, 44100Hz sample rate, approx. 500 KB/minute
Operating temperature	-20 °C to +55 °C

Charging system CS25/CS56

Supply voltage	220 - 240V AC, 50/60 Hz
Charging rate with simultaneous charging for all 56 slots	1.2A
Dimensions (LxWxD)	51 x 42 x 20 cm
Operating temperature	0 °C to +40 °C



Warning:

- The device may only be opened by the manufacturer. Improper use can result in the Li-Po battery exploding!
- Old and/or defective devices must be disposed of separately from domestic waste!
- The internal batteries may only be charged using suitable charging systems (CS25/CS56) (limited SELV source, 5 V/700 mA per device).
- The devices may only be used in dry environments and must be protected against humidity!